



**Rolled Beams UPN**

Travi UPN  
UPN Träger  
Poutrelles UPN  
Perfil UPN

**DIN 1026-1**  
**NF A 45-202**  
**EN 10279**

		<b>h</b>	<b>b</b>	<b>s</b>	<b>t</b>	<b>kg/m</b>	<b>Product lengths - Herstellungslängen - Lunghezze di fabbricazione - Longueurs de fabrication - Longitudes de fabricación</b>
<b>Type</b>	<b>UPN 80</b>	80	45	6	8	8,65	
	<b>UPN 100</b>	100	50	6	8,5	10,6	
	<b>UPN 120</b>	120	55	7	9	13,3	
	<b>UPN 140</b>	140	60	7	10	16,0	
	<b>UPN 160</b>	160	65	7,5	10,5	18,8	6m ▶ 25m (-0/+100 mm)
	<b>UPN 180</b>	180	70	8	11	22,0	
	<b>UPN 200</b>	200	75	8,5	11,5	25,3	
	<b>UPN 220</b>	220	80	9	12,5	29,4	
	<b>UPN 240</b>	240	85	9,5	13	33,2	
	<b>UPN 260°</b>	260	90	10	14	37,9	
	<b>UPN 280°</b>	280	95	10	15	41,8	
	<b>UPN 300°</b>	300	100	10	16	46,2	

on request - a richiesta - auf Anfrage - sur demande - a solicitud

**Process tolerances**  
**Tolleranze di fabbricazione**  
**Herstellungstoleranzen**  
**Tolérances de fabrication**  
**Tolerancias de fabricación**

h (mm)	65 < h ≤ 200	± 2,0	65 < h ≤ 200	± 3,0
	b ≤ 50	± 1,5	50 < b ≤ 100	± 2,0
s (mm)	s ≤ 10	± 0,50		
	t ≤ 10	-0,5 / + *	10 < t ≤ 15	-1,0 / + *
t (mm)			t > 15	-1,5 / + *

\* plus tolerances are limited by the permissible exceeding of weight