



Sharp edged equal angles

Angolari ad ali uguali con spigoli vivi
 Gleichschenklige scharfkantige Winkel
 Cornières à ailes égales et à angles vifs
 Angulares de lados iguales de aristas vivas

DIN 1022

| | | t (mm) | | | | | | | | | | | | | |
|----------------|--------------------|--------|------|------|------|------|------|------|------|------|------|----|--|--|--|
| | | 3 | 3,5 | 4 | 4,7 | 5 | 5,8 | 6 | 6,8 | 8,8 | 10,8 | 11 | | | |
| axa (mm) | 20x20 | 0,87 | 1,00 | 1,13 | | | | | | | | | | | |
| | 25x25 | 1,11 | 1,28 | 1,44 | | | | | | | | | | | |
| | 30x30 | 1,34 | 1,55 | 1,76 | 2,04 | 2,16 | | | | | | | | | |
| | 31,2x31,2 | 1,40 | 1,62 | 1,83 | 2,13 | 2,25 | 2,58 | 2,66 | | | | | | | |
| | 35x35 | 1,58 | 1,83 | 2,07 | 2,41 | 2,55 | 2,92 | 3,01 | | | | | | | |
| | 40x40 | 1,81 | 2,10 | 2,39 | 2,78 | 2,94 | 3,38 | 3,49 | | | | | | | |
| | 41,2x41,2 | | 2,17 | 2,46 | 2,87 | 3,04 | 3,49 | 3,60 | 4,04 | | | | | | |
| | 50x50 | | | 3,01 | 3,52 | 3,73 | 4,29 | 4,43 | 4,98 | | | | | | |
| | 51,2x51,2 | | | 3,09 | 3,60 | 3,82 | 4,40 | 4,54 | 5,10 | | | | | | |
| | 60x60 | | | | | 4,51 | 5,20 | 5,37 | 6,04 | | | | | | |
| | 61,2x61,2 | | | | | 4,61 | 5,31 | 5,48 | 6,17 | | | | | | |
| | 81,2x81,2 | | | | | | | 7,37 | 8,31 | 10,6 | 12,9 | | | | |
| | 101,2x101,2 | | | | | | | 9,23 | 10,4 | 13,3 | 16,2 | | | | |
| | 101,5x101,5 | | | | | | | 9,23 | 10,4 | 13,3 | 16,2 | | | | |
| 102x102 | | | | | | | 9,33 | 10,5 | 13,5 | 16,4 | 16,7 | | | | |

(kg/m)

Product lengths

Lunghezze di fabbricazione 6m ► 15m (-100/+100 mm)
 Herstellungslängen
 Longueurs de fabrication
 Longitudes de fabricación

Process tolerances

| | | | | |
|--|--------|-----------------|-----------------------|------------------------|
| Tolleranze di fabbricazione Herstellungstoleranzen Tolérances de fabrication Tolerancias de fabricación | a (mm) | a ≤ 50 ± 1,0 | 50 < a ≤ 100 ± 2,0 | 100 < a ≤ 150 ± 3,0 |
| | t (mm) | t ≤ 5 ± 0,50 | 5 < t ≤ 10 ± 0,75 | 10 < t ≤ 15 ± 1,00 |